



WARNING SIGN W/SUBPLATE
200' IN ADVANCE OF
ROUNDBOUT (TYP)
(CITY OF WILMINGTON DESIGN)

MUTCD W16-7P SUBPLATE IN
FLUORESCENT YELLOW-GREEN (TYP)

MUTCD W11-2 IN
FLUORESCENT YELLOW-GREEN
(TYP)

2' MOUNTABLE
CURB

4" WIDE YELLOW
EDGELINE (TYP)

MUTCD W13-1
SUBPLATE (TYP)

4" WIDE WHITE
MINI-SKIPS 2" LONG
WITH 4' GAP (TYP)

8" WIDE YELLOW LINES
@ 45° (typ)

R44'
(TYP)

MUTCD
R6-1
(TYP)

4" WIDE DOUBLE YELLOW
CENTERLINE W/YELLOW
REFLECTORS (TYP.)

MUTC R1-2
(TYP)

R25'
(TYP)

10' WIDE HIGH-VISIBILITY CROSSWALK
24" WIDE WHITE LINES WITH
24" GAP (TYP)

NOTE: ALL SIGNS MOUNTED
AT 7' EXCEPT FOR ONE WAY
SIGNS, WHICH ARE TO BE
MOUNTED AT 5'

STANDARD DETAIL

PAVEMENT MARKINGS
ROUNDBOUT



CITY OF WILMINGTON ENGINEERING
PO BOX 1810
WILMINGTON, NC 28402
(910) 341-7807

DATE:	2003
DRAWN BY	RLB
CHECKED BY	JRF
SCALE	NOT TO SCALE

SD 11-14