



1. BRICK TYPE, SIZE AND PATTERN SHALL BE COORDINATED WITH CITY OF WILMINGTON. TYPICAL BRICK PAVER 4"x8"x2-3/4" HERRINGBONE PATTERN. RUMBLED COURTYARD, FULL RANGE COLOR, BRICK BY PINE HALL.
2. PAVERS SHALL MEET OR EXCEED ASTM C1272 STANDARD SPECIFICATION FOR HEAVY VEHICULAR PAVING BRICK, TYPE "F".
3. CONCRETE HEADER TO BE 3000 PSI, BROOM FINISH, 1/2" RADIUS ON EDGES AND FLUSH WITH ASPHALT AND PAVERS. CONTROL JOINTS AT ±5' O.C. (EQUAL SPACING). CONCRETE TO BE POURED AFTER COMPACTION OF STONE SUB-BASE.
4. WELDED WIRE MESH REINFORCEMENT SHALL BE 6x6 WITH 4.0/4.0 AND FREE OF OIL, DIRT AND DEFECTS AND SHALL BE PROTECTED FROM DAMAGE. WIRE SPLICES SHALL OVERLAP 12 INCHES AND BE TIED TOGETHER AND SUPPORTED IN PLACE.

STANDARD DETAIL

DATE: NOVEMBER, 2011

DRAWN BY JSR

CHECKED BY B.D.R., P.E.

SCALE NOT TO SCALE

BRICK CROSSWALK



CITY OF WILMINGTON ENGINEERING
 PO BOX 1810
 WILMINGTON, NC 28402
 (910) 341-7807

SD 3-102