SCM Drainage Basin #: \_\_\_\_\_

## Sand Filter Operation and Maintenance Agreement

I will keep a maintenance record on this SCM. This maintenance record will be kept in a log in a known set location. Any deficient SCM elements noted in the inspection will be corrected, repaired or replaced **immediately**. These deficiencies can affect the integrity of structures, safety of the public, and the pollutant removal efficiency of the SCM.

Important maintenance procedures:

- The drainage area will be carefully managed to reduce the sediment load to the sand filter.
- The sedimentation chamber or forebay will be cleaned out whenever sediment depth exceeds six inches.
- Once a year, sand media will be skimmed.
- The sand filter media will be replaced whenever it fails to function properly after maintenance.

The sand filter will be inspected **quarterly and within 24 hours after every storm event greater than 1.5 inches**. Records of operation and maintenance will be kept in a known set location and will be available upon request.

Inspection activities shall be performed as follows.	Any problems that are found shall
be repaired immediately.	

SCM element:	Potential problem:	How to remediate the problem:
Entire SCM	Trash/debris is present.	Remove the trash/debris.
Adjacent pavement (if applicable)	Sediment is present on the pavement surface.	Sweep or vacuum the sediment as soon as possible.
Perimeter of sand filter	Areas of bare soil and/or erosive gullies have formed.	Regrade the soil if necessary, to remove the gully, and then plant a ground cover and water until it is established. Provide lime and a one-time fertilizer application.
	Vegetation is too short or too long.	Maintain vegetation at an appropriate height.
Flow diversion structure	The structure is clogged.	Unclog the conveyance and dispose of any sediment offsite.
	The structure is damaged.	Make any necessary repairs or replace if damage is too large for repair.
The inlet device	The pipe is clogged.	Unclog the pipe. Dispose of the sediment offsite.
	The pipe is cracked or otherwise damaged.	Replace the pipe.

SCM element:	Potential problem:	How to remediate the problem:
Forebay or pretreatment	Sediment has accumulated to a	Search for the source of the
area	depth of greater than six inches.	sediment and remedy the
		problem if possible. Remove
		the sediment and stabilize or
		dispose of it in a location where
		it will not cause impacts to
		streams or the SCM.
	Erosion has occurred.	Provide additional erosion
		protection such as reinforced
		turf matting or riprap if needed
		to prevent future erosion
		problems.
	Weeds are present.	Remove the weeds, preferably
		by hand. If a pesticide is used,
		wipe it on the plants rather than
		spraying.
Filter bed and	Water is ponding on the surface	Check to see if the collector
underdrain collection	for more than 24 hours after a	system is clogged and flush if
system	storm.	necessary. If water still ponds,
		remove the top few inches of
		filter bed media and replace. If
		water still ponds, then consult
		an expert.
Outlet device	Clogging has occurred.	Clean out the outlet device.
		Dispose of the sediment offsite.
	The outlet device is damaged	Repair or replace the outlet
		device.
Receiving water	Erosion or other signs of damage	Contact the NC Department of
	have occurred at the outlet.	Environment and Natural
		Resources Regional Office.

I acknowledge and agree by my signature below that I am responsible for the performance of the maintenance procedures listed above. I agree to notify the City of Wilmington of any problems with the system or prior to any changes to the system or responsible party.

Project name:	
SCM drainage basin number:	
Print name:	
Title:	
Address:	
Phone:	
Signature:	
Date:	
the lots have been sold and a resider	d not be a homeowners' association unless more than 50% of nt of the subdivision has been named the president. , a Notary Public for the State of
	, do hereby certify that
-	personally appeared before me this
	, and acknowledge the due execution of the
forgoing sand filter maintenance requ	irements. Witness my hand and official seal,
SEAL My commission expires	